



NORMATIVE DOCUMENTS

Lightning test: IEC 61312-1 grade III-IV

Waterproof test:
IP67 (acc.to IEC 529)

Temperature range: -50° +80°C

Contact resistance: ≤1mΩ

ACCEPTANCE TEST

Visual and dimensional control
on samples.

Rif.	DESCRIPTION
1	Tin Plate Copper Contact Bar (special lug)
2	Tin Copper Tube ø3mm Length 0.5m
3	Vinyl Mastic Tape 016mm² thickness Length 30cm
4	PVC Black UV Proof Tape Length 2m
5	Screw UNI 5931 M8x20
6	Grower UNI 1751 M8
7	Nut UNI 5588 M8
8	Cable section 16mm² Length 600mm
9	Eyelet Terminal 16mm²
ASSEMBLY INSTRUCTION (93.100.006-130) PE BAG 220X300mm	

				Dis: / Drawing:		Contr: / Check:	
1	EMESSO DISEGNO / FIRST ISSUE	21/05/15					
N°	REVISIONE / REVISION	DATA	DIS.	CONT.	APPR.	DATA/DATE	U.M. mm
DENOMINAZIONI / DESCRIPTION		DATE	DRAWN	CHECK	APPR.	21/05/15	Form. Scala/scale A4 1:1
GROUNDING KIT FOR CABLE from CNT300/400; LMR300/400						N.DISEGNO DRAWING N°	