## Product data sheet Characteristics

## NSYS3D81030P

Spacial S3D plain door with mount.plate. H800xW1000xD300.IP66 IK10 RAL7035.





## Main

| IVIAIII                     |  |
|-----------------------------|--|
| Range                       | Spacial  |
| Product name                | Spacial S3D  |
| Application                 | Multi-purpose  |
| Category                    | Compact enclosure  |
| Enclosure nominal height    | 800 mm   |
| Enclosure nominal width     | 1000 mm  |
| Enclosure nominal depth     | 300 mm   |
| Door type                   | Plain  |
| Mounting plate description  | Plain  |
| Type of gland plate         | Standard   |
| Installation accessory type | Wall-mounting  |
| Device composition          | body     cable gland plate     mounting plate     door with lock |

## Complementary

| Body type                   | Single piece body Gutter-shaped front rail double sheet thickness                 |          |  |
|-----------------------------|---|----------|--|
| Number of doors             | Front face: 1 door(s)   |          |  |
| Door opening side           | Reversible (120 °)  |          |  |
| Lock type                   | 3 points lock, 3 mm double-bar  |          |  |
| Accessibility for operation | Front   | <u> </u> |  |
| Removable parts             | Door by hinges<br>Cable gland plate by screws<br>Mounting plate by fixing element |          |  |
| Material                    | Enclosure: steel Mounting plate: galvanised steel                                 |          |  |
| Surface finish              | Enclosure: epoxy-polyester powder   | E        |  |

| Colour                   | Enclosure: grey (RAL 7035)                                 |  |  |  |
|--------------------------|--|--|--|--|
| Standards                | IEC 62208  |  |  |  |
| Product certifications   | GL   |  |  |  |
|                          | UL   |  |  |  |
|                          | LR   |  |  |  |
|                          | DNV  |  |  |  |
|                          | CUL<br>BV  |  |  |  |
|                          | <del>-</del> :   |  |  |  |
| Net weight               | 52 kg  |  |  |  |
| Environment              |  |  |  |  |
| IP degree of protection  | IP66 conforming to IEC 60529                               |  |  |  |
| IK degree of protection  | IK10 conforming to IEC 62262                               |  |  |  |
| Packing Units            |  |  |  |  |
| Package 1 Weight         | 52.000 kg  |  |  |  |
| Package 1 Height         | 820.000 mm   |  |  |  |
| Package 1 width          | 1040.000 mm  |  |  |  |
| Package 1 Length         | 360.000 mm   |  |  |  |
| Offer Sustainability     |  |  |  |  |
| Offer Sustainability     | Our Pour' a sud d  |  |  |  |
| Sustainable offer status | Green Premium product                                      |  |  |  |
| REACh free of SVHC       | Yes  |  |  |  |
| EU RoHS Directive        | Pro-active compliance (Product out of EU RoHS legal scope) |  |  |  |

| Contractual | warranty |
|-------------|----------|

RoHS exemption information

China RoHS Regulation

**Environmental Disclosure** 

Mercury free

| Contractual warranty |           |  |  |
|----------------------|-----------|--|--|
| Warrantv             | 18 months |  |  |

Product out of China RoHS scope. Substance declaration for your information

**EU RoHS Declaration** 

China RoHS declaration

**Product Environmental Profile** 

Yes

Yes