# Product data sheet Characteristics

## SE125A16

LoadCentre KQ - distribution board - A type - single phase - 125A - 16 ways



#### Main

D	A - 1' O	
Range	Acti 9	
Product name	Load centre KQ II A	
Product or component type	Distribution board	
Device application	Distribution	
Enclosure type	Standard	
Door type	Overall	
Provided equipment	Enclosure	
	Door	
	Front cover	
	Pan assembly	
	Earth terminal block 25 mm²	
	Shielded neutral bar 25 mm²	

#### Complementary

Enclosure mounting	Surface	
[le] rated operational current	125 A at 230/240 V AC	
Incomer device	Switch disconnector - 2P Terminal block - 2P RCCB - 30 mA - 2P RCCB - 100 mA - 2P RCCB - 300 mA - 2P	
Protection device type	Miniature circuit breaker (MCB) (plug-on type) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on- type) as outgoer	
Number of ways	16 ways (1P) outgoer	
Cable entry	Top and bottom: knock-out side: knock-out	
Height	270 Mm	
Width	456 Mm	
Depth	127 Mm	

#### **Environment**

IP degree of protection	IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
	ii 3x external comorning to be Ett 00329

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

### Contractual warranty

	·
Warrantv	18 months

Product Life Status : Commercialised