



Main

| | |
|---------------------------|-------------|
| Product or component type | Neutral bar |
| Enclosure type | Standard |
| Door type | Overall |

Complementary

| | |
|--------------------------------|--|
| [Ie] rated operational current | 250 A at 400/415 V AC |
| Breaking capacity | 25 kA |
| Poles description | 3P + N |
| Protection device name | IC60H |
| Product destination | Distribution board |
| Number of ways | 4 ways outgoer |
| Provided equipment | Neutral bar Busbar link 4 Cover |
| Enclosure material | Steel |
| Surface treatment | Epoxy |
| Surface finish | Powder paint |
| IP degree of protection | IP2x internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529 |
| IK degree of protection | IK05 conforming to BS EN 60529 |
| Colour | White (RAL 9001) |
| Height | 484 mm |
| Depth | 138 mm |

Environment

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -35...70 °C |
| Ambient air temperature for storage | -40...80 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|