

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 1

Compilation date: 13/12/10

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FIREFOAM B2 - GUN GRADE AND HAND HELD

Product code: B2FIREGUN, B2FIREHAN

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND **Tel:** 0044 113 240 3456

Fax: 0044 113 240 0024
Email: pault@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20

Classification under CLP: Carc. 2: H351; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2:

H373; STOT SE 2: H371

Most important adverse effects: Extremely flammable. Irritating to eyes, respiratory system and skin. Limited evidence of

a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Harmful:

danger of serious damage to health by prolonged exposure through inhalation.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H351: Suspected of causing cancer. H371: May cause damage to organs .

H373: May cause damage to organs through prolonged or repeated exposure.

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 2

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard





Precautionary statements: P102: Keep out of reach of children.

P280: Wear protective gloves. P260: Do not breathe fume.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice/attention.

P309+311: IF exposed or if you feel unwell: Call a POISON CENTER or doctor.

P314: Get medical advice if you feel unwell.

Label elements under CHIP:

Hazard symbols: Extremely flammable.

Harmful.





Risk phrases: R12: Extremely flammable.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

Safety phrases: S2: Keep out of the reach of children.

S36/37: Wear suitable protective clothing and gloves.

S46: If swallowed, seek medical advice immediately and show this container or label.

S51: Use only in well-ventilated areas.

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources

of ignition - No smoking. Keep out of the reach of children.

Person already sensitised to diisocyanates may develop allergic reactions when using

this product

Persons suffering from asthma, eczema or skin problems should avoid contact,

including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 3

mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-966-0	101-68-8	Xn: R40; Xn: R20; Xn: R48/20; Xi:	Carc. 2: H351; Acute Tox. 4: H332; Eye	10-30%
		R36/37/38; Sens.: R42/43	Irrit. 2: H319; STOT SE 3: H335; Skin	
			Irrit. 2: H315; Resp. Sens. 1: H334;	
			Skin Sens. 1: H317; STOT SE 2:	
			H371; STOT RE 2: H373	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor. Remove/soften cured foam from skin with petroleum jelly or

via constant softening with hot soapy water

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 4

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour

mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific

substance. Do not use equipment in clean-up procedure which may produce sparks.

Allow product to solidify and remove it by mechanical means. Remove uncured foam

with acetone Transfer to a closable, labelled salvage container for disposal by an

appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 5

sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these paramaters will dramatically reduce shelf life and invalidates all product warrenties.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA:	15 min. STEL:	8 hour TWA:	15 min. STEL:
UK	0.02 mg/m3	0.07 mg/m3	-	•

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration

is above OES or if ventilation is poor Self-contained breathing apparatus must be

available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: Yellow

Odour: Barely perceptible odour

Solubility in water: Insoluble

Viscosity: Highly viscous

Flash point°C: -4

9.2. Other information

Section 10: Stability and reactivity

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 6

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion

emits toxic fumes of hydrogen cyanide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis	
Irritation	OPT INH DRM	Hazardous: calculated	
Sensitisation	INH DRM	Hazardous: calculated	
Repeated dose toxicity	INH	Hazardous: calculated	

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 7

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: VOC 20% w/w

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity. Not dangerous to ozone layer (1999/45/EC)

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J L47 of

16/2/2002): 08 05 01 (waste isocyanates)

Disposal of packaging: Waste material code packaging (91/689/EEC); Council decision 2001/118/EC, O.J L47

of 16/2/2001) 15 01 10 (packaging containing residues of or contaminated by

dangerous substances)

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eve irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R12: Extremely flammable.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.