716F-SCF12-D01



7-16 DIN Female Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium,

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment.

Cable interface while simplifying and speeding up connector attachment.

All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions. Sealing against outer conductor and jacket by means of threaded gasket and 360 compression fit. Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.



OMNI FIT™ Premium Connectors

FEATURES / BENEFITS


Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction

Technical Features		
GENERAL SPECIFICATIONS		
Transmission Line Type		Coaxial Cable
Cable Size		1/2"
Cable Type		Foam Dielectric
Model Series		SCF12-50 Series
Connector Interface		7-16 DIN
Connector Type		OMNI FIT™ PREMIUM Straight
Sealing Method		Threaded Gasket + 360° Compression
Gender		Female
ELECTRICAL SPECIFICATIONS		
Nominal Impedance	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-163; typical -167
Maximum Frequency	GHz	3.7
VSWR, Return Loss	VSWR (dB)	0 < f ≤ 1.0 GHz: 1.02 (40.0) 1.0 < f ≤ 2.7 GHz: 1.03 (36.6) 2.7 < f ≤ 3.7 GHz: 1.06 (30.7)
MECHANICAL SPECIFICATIONS		
Plating Outer/Inner		NiTin/Silver
Length	mm (in)	486 (1.9)
Outer Diameter	mm (in)	28.8 (1.1)
Weight	kg (lb)	0.11 (0.24)
Inner Contact Attachment		Spring Finger
Outer Contact Attachment		360° clamping
ACCESSORIES		
Wrench size front	mm (in)	22 (7/8)
Wrench size rear	mm (in)	22 (7/8)
Trimming Tool		TRIM-12-S06 TRIM-SCF12-D01-A
TESTING AND ENVIRONMENTAL		
Waterproof Level		IP68

716F-SCF12-D01 REV: G REV DATE: 10.Jan.2014 www.rfsworld.com



7-16 DIN Female Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium,



716F-SCF12-D01_DRW.png

External Document Links

Notes

Installation Instruction

716F-SCF12-D01 REV: G REV DATE: 10.Jan.2014 www.rfsworld.com