

# Discrete feeders for single RRH

## FTTA Fiber-To-The-Antenna feeder



### Features

- FTTA feeders for all common RRH models and systems
- Ruggedised design and installation proof
- Standard assemblies and customised lengths available with short lead-time
- Cable diameter 4.8 mm, 5.5 mm or 7 mm
- All cables rodent resistant
- All cable assemblies factory-terminated and tested
- UL (OFNR) and Anatel approved cables available on request

### Cable specifications

Outer cable diameter	4.8 mm	5.5 mm	7 mm
Jacket material	LSFH™	LSFH™	LSFH™
Maximum tensile strength (during installation/service)	300/500 N	500/1000 N	650/1000 N
Cable crush resistance (short-term/long-term)	200/400 N/cm	200/400 N/cm	300/1000 N/cm
Temperature range	-40 °C to +90 °C	-40 °C to +80 °C	-40 °C to +80 °C
Flame resistance	IEC 60332-1, IEC 60332-3-24, UL1666		
UV resistant	yes	yes	yes



### HUBER+SUHNER cables are deployed on a global scale

Year by year, HUBER+SUHNER produces tens of thousands of FTTA feeder cables and is a leading global supplier to major system vendors and operators. Our customers value our quality products which are manufactured on all continents close to the local markets.

HUBER+SUHNER is also an innovation leader for remote radio interfaces and is the owner of globally successful products like ODC, Q-ODC and Q-XCO.



# Discrete feeders for single RRH

FTTA Fiber-To-The-Antenna feeder

## Ordering information

FullAXS feeder with 4.8 mm cable, singlemode bend insensitive fiber



Length	Item no.	Length	Item no.
1 m	84137909	50 m	84137917
2 m	84137910	60 m	84137918
5 m	84137911	70 m	84137919
10 m	84137912	80 m	84137920
15 m	84137913	90 m	84137921
20 m	84137914	100 m	84137922
30 m	84137915	125 m	84137923
40 m	84137916	150 m	84137924

ODC feeder with Ø 5.5 mm cable



Length	Item no. singlemode bend insensitive fiber	Item no. multimode
1 m	84122151	84124943
2 m	84122152	84124942
5m	84078725	84078739
10 m	84078726	84078740
15 m	84078727	84078741
20 m	84078728	84078742
30 m	84078729	84078743
40 m	84078730	84078744
50 m	84078731	84078745
60 m	84078732	84078746
70 m	84078733	84078747
80 m	84078734	84078748
90 m	84078735	84078749
100 m	84078736	84078750
125 m	84078737	84078751
150 m	84078738	84078752

ODC feeder also available with 7 mm cable diameter or as 1-fiber version.