



All dimensions are in mm; tolerances according to ISO 2768 c-H

**Main Features**

Excel Category 6 U/UTP Outdoor patch leads are manufactured in 24 AWG High Quality FULL COPPER cable and tested to ISO 11801 & EN 50288 & TIA EIA-568-B.2-1 ETL/3P requirements for patch cord assemblies and provide optimum performance levels for structured cabling installations.

Outdoor rated cables are suitable for burying or being left exposed to the elements due to the jacket. The PE jacket is weatherproof and UV resistant ensuring they do not erode over the years. We recommend a trunking if you are burying these cables as they are not spade proof.

**Product Specifications**

Cable type	U/UTP
Category	6
Length	X m
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Outer sheath colour	Black
Outer sheath material	Low Smoke Polyethylene (Water tight and UV resistant)
Cable OD	6mm
Strain relief boot colour	Black

This document is protected by copyright. GCA Ltd

RF\_35/06.10/1.0

# Technical Data Sheet



## CAT6 External Patch Leads

## CAT6-EXT-X

### Part Numbers of Cables

Part Number	Length
CAT6-EXT-1M	1M
CAT6-EXT-2M	2M
CAT6-EXT-3M	3M
CAT6-EXT-5M	5M
CAT6-EXT-10M	10M
CAT6-EXT-15M	15M
CAT6-EXT-20M	20M
CAT6-EXT-30M	30M

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
L.Wesley	01/01/23	L.Wesley	01/01/23	001	10001007	S.W	01/01/23
GCA Ltd Ronell Place, 41A Shire Hill Industrial Estate, Saffron Walden, Essex, CB11 3AQ www.gca.co.uk				Tel – 01799 516016 Email – sales@gcald.co.uk			Page 2/2