
Technical Data Sheet



Earth Bars





EBCX



All dimensions are in mm; tolerances according to ISO 2768 m-H

Description

GCA earth bars provide a convenient common earthing point for electrical installations. Our standard earth bars are manufactured from 50mm x 6 mm hard drawn copper bar and come complete with M10 fittings and insulators. The PVC base makes our earth bars lighter and easier to handle as well as being entirely corrosion proof.

Recommended fixing by countersunk wood screw 1 1/2" x No. 12 and No. 12 wall plug.

Part Number	No Terminations	L (mm)	W (mm)	H (mm)	Unit Weight (kg)	Pack Qty
EBC004	4	300	90	60	1.45	1
EBC006	6	400	90	60	2.00	1
EBC008	8	500	90	60	2.30	1
EBC010	10	650	90	60	3.20	1
EBC012	12	750	90	60	4.00	1
EBC014	14	850	90	60	4.90	1

Environmental Data

Material

50 x 6mm hard drawn copper bar to BS EN 13601 Bar:

Base: Metal

Fittings: M10 brass hexagon head set screws, nuts & washers

Standard: BS 7430 **Current Capacity** 700A Hole Centres 35mm

Draft	Date	Approved	Date	
L.Wesley	01/06/23	L.Wesley	01/06/23	

	Rev. Engineering change number		Name	Date
	1	10001034	M.W	01/06/23
1				

GCA Ltd

Ronell Place, 41A Shire Hill Industrial Estate,

Saffron Walden, Essex, CB11 3AQ

www.gca.co.uk

Tel - 01799 516016 Email - sales@gcaltd.co.uk Page 1/2

35/06.10/1.0