

ALL PURPOSE SILICONE SPRAY



Colour	Product Code	Pack Size	Box Qty
-	SILSPRAY	400ml	12

Product Description

EVERBUILD ALL- PURPOSE SILICONE SPRAY is a dry silicone lubricant and mould release agent for the easing of friction between two surfaces.

ALL- PURPOSE SILICONE SPRAY is ideal for use in mould making/release industries, to ease installation of rubber and EPDM gaskets to window and door frames and has 100's of uses around the home, garage, workshop and industry. ALL-PURPOSE SILICONE SPRAY will also enhance the appearance of vinyl and hard surfaces such as car dashboards etc, where the dry-bright finish will eliminate the need to polish.

Benefits

- Enables friction to be reduced between most surfaces
- Eliminates noise and squeak
- Leaves a bright gloss finish to vinyl
- ALL-PURPOSE SILICONE SPRAY meets BS6920 for use in contact with potable drinking water.

Areas For Use

- Multitude of uses in the mould making and mould release industries
- Making easy the installation of EPDM gaskets to window and doorframes.
- Restoring the black gloss finish to car vinyl trim without the need for polishing
- As a general high quality spray lubricant.

Limitations

Do not ingest. Pressurized container – Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on a naked flame or incandescent material. Test small area of surface to be coated for compatibility before use. As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice

Application

Shake the can and spray as required directly onto surface(s) to be lubricated. When used as a mould release agent, spray liberally onto mould and allow to dry.

COVERAGE: 120-250g/m²

Health & Safety

Extremely flammable

Keep out of reach of children

If swallowed, seek medical advice immediately and show this container/label.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Do not breathe vapour/spray.

Keep away from sources of ignition – no smoking.

Storage

STORAGE: Store in original packaging away from direct sunlight and sources of ignition between 5 and 25°C.

Shelf Life

12 months.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.