

Nylon 6.6 Cable Ties: Non-Releasable



Specification:

- Material: High quality virgin Nylon 6.6
- Flame Resistance: In accordance with UL94V2
- Strength: Tensile strength MIL 23190E
- Temperature Range: For continuous use - 40°C to +85°C
- Ul: Approved
- Colours: Natural and Black.
- Pack Sizes: Cable ties up to and including 200mm in length, available in pack sizes of 100 or 1000 pieces. Please specify when ordering. Cable ties over 200mm in length are packed in 100's.

Cable Ties				
Part Number	Length (mm)	Width (mm)	Maximum Bundle Diameter (mm)	Minimum Tensile Strength (KG)
HFC80	80	2.5	15	8
HFC100	100	2.5	18	8
HFC120	120	4.8	24	22
HFC140	140	3.6	33	18
HFC160L	160	2.5	40	8
HFC160	160	4.8	38	22
HFC200L	200	2.5	50	8
HFC200I	200	3.6	50	18
HFC200	200	4.8	50	22
HFC250	250	4.8	63	22
HFC300L	300	3.6	76	18
HFC300	300	4.8	76	22
HFC365	370	4.8	102	22
HFC430	430	4.8	110	22
HFC530	530	4.8	140	22
HFC150H	150	7.6	36	55
HFC200H	200	7.6	50	55

HFC240H	240	7.6	66	55
HFC300H	300	7.6	76	55
HFC370H	370	7.6	100	55
HFC430H	430	9.0	110	75
HFC530H	530	9.0	140	75
HFC710H	710	9.0	190	75
HFC940H	940	9.0	280	75
HFC1220H*	1220	9.0	365	75
HFC580EH	580	12.7	152	113

* Please specify natural or black when ordering.

* Only available in black.

*Although Nylon cables ties have a wide operating temperature it is not recommended that they should be stored or installed at extremes of temperature.