

Copper Tube Crimp Terminals



Product Overview

- All copper tubes terminals have bell mouth entry for ease of cable insertion.
- All terminals have inspection holes to check cable is properly inserted before crimping
- Copper tube splices, four hole transformer fixing, long palm, right angle, blank terminals, copper pins, dissimilar copper splices and flag terminals also available on request.
- Sizes above 400mm² available on request.
- Other Stud sizes available on request.

Specification:

Material: High Conductivity copper to BS 2871

Purity: > 99.9%

Coating: Bright electro-tin plating to BS 1872.

Entry: Bell-mouth easy entry.

Barrels: Internal Barrel diameters suit standard cables as defined in BS 6360.

Copper Tube Terminals

Part No.	Conductor Cross-sectional Area (mm ²)	Stud Size (mm) (Please Specify) (Eg. DX 10-5)
DX1.5	1.5	4, 5
DX2.5	2.5	4, 5, 6
DX4	4	4, 5, 6
DX6	6	4, 5, 6, 8, 10
DX10	10	5, 6, 8, 10, 12
DX16	16	5, 6, 8, 10, 12
DX25	25	5, 6, 8, 10, 12
DX35	35	6, 8, 10, 12
DX50	50	6, 8, 10, 12, 14, 16
DX70	70	6, 8, 10, 12, 14, 16
DX95	95	8, 10, 12, 14, 16
DX120	120	8, 10, 12, 14, 16
DX150	150	10, 12, 14, 16, 20
DX185	185	10, 12, 14, 16, 20
DX240	240	10, 12, 14, 16, 20
DX300	300	10, 12, 14, 16, 20
DX400	400	10, 12, 14, 16, 20