

Outdoor Cable Glands



Application: CW Brass cable glands are suitable for Steel Wired Armour cables. Outer seal grips sheath to achieve weather proof seal. Separate armour lock ring ensures armour clamping. They are suitable for external use.

Standards: BS6121 Part 1

IP66 (Ingress Protection — dust tight, with a vacuum applied to the product, protected against powerful water jets.)

Gland Material: Brass

Cable Type: Steel Wire Armour

Armour Clamping: Two Part Armour Lock (Three Part Option Available)

Seal Material: Thermoplastic Elastomer

Gland Selection Chart for PVC/SWA/PVC Cables to BS 5467 & XLPE/LSZH/SWA/SLZH Cables to BS 6724

No. Of Cores	Cable Area mm ²																
	1.5	2.5	4	6	10	16	25	35	50	70	95	120	150	185	240	300	400
1	-	-	-	-	-	-	-	-	20	20	25	25	32	32	32	40	40
2	20/16	20S	20S	20S	20	25S	25S	25	25	32	32	40	40	50S	50	63S	63S
3	20/16	20S	20S	20	20	25	32	32	32	32	40	50S	50S	50	63S	63	75S
4	20S	20S	20	20	25	25	32	32	32	40	50S	50	50	63S	63	75S	75
5	20S	20S	20	20	25	25	32	32									
7	20S	20	20	25	25	32	40										
10	20	25	25	32	32												
12	20	25	25	32	32												
19	25	25	32														
27	32	32	40														
37	32	40	40														
48	40	40	50S														

This selection chart is given for guidance only. We advise cable diameter to be measured where possible before purchasing gland kit to confirm compatibility.