

## Pre-Insulated Crimp Terminals: Rings

### Product Overview

- A complete range of pre-insulated terminals that combine high quality with competitive pricing
- High grade PVC insulation makes crimping easy whilst ensuring complete integrity of termination
- VR indicates 'Vibration Resistant' – Extra copper ring within the crimp terminal
- Available in packs of 100 or 1000 pieces as standard
- Red Insulation: conductor size 0.5-1.5mm<sup>2</sup>/ 22-16awg
- Blue Insulation: conductor size 1.5-2.5mm<sup>2</sup>/ 16-14awg
- Yellow Insulation: conductor size 4.0-6.0mm<sup>2</sup>/ 12-10awg
- UL approval number: E163810

Terminals – Imperial/Metric Conversion	
Imperial	Metric (mm)
8BA	2
6BA	3
4BA	3.5
3BA	4
2BA	5
0BA	6
5/16"	8
3/8"	10

Conversions (continued)	
Imperial	Metric (mm)
1/2"	12
9/16"	14
5/8"	16
11/16"	18
3/4"	20
7/8"	22
1"	25



Ring Terminals		
Part Number	Stud Size (mm)	Insulation Colour
RR32	3	Red
RR37	3.5	Red
RR43	4	Red
RR53	5	Red
RR64	6	Red

RR84	8	Red
RR105	10	Red
BR32	3	Blue
BR37	3.5	Blue
BR43	4	Blue
BR53	5	Blue
BR64	6	Blue
BR84	8	Blue
BR105	10	Blue
BR120	12	Blue
YR43	4	Yellow
YR53	5	Yellow
YR64	6	Yellow
YR84	8	Yellow
YR105	10	Yellow
YR120	12	Yellow